

# SP-ROXX BLINDER

EFFECT FIXTURE



## POWER & PHYSICAL

- Input voltage: AC 110V-240V 50/60Hz
- Rated power: 600W optical
- Size: 502 × 288 × 195 mm
- Net weight: 9 kgs
- Aluminum alloy die-casting structure

## LIGHT SOURCE

- Light source: 2X300W LED RGBAWW (1800K-10000K)
- Beam angle: 65°
- Light spot angle: 97°
- Light source life: 20000 H
- Color rendering index: 95

## COLOR, OPTICS & EFFECTS

- Uniform color mixing system can adjust
- the effect of tungsten filament lamp
- 8 types of built-in processes to choose
- Fast electronic strobe: 1-20 Hz
- Dimming modes: 5 kinds

## CONTROL

- Control channel : 2 / 4 / 9 / 6 / 10 / 14 / 13 / 22 / 24 / 33 / 10 / 12 / 17 / 28 / 41
- Protocol: Standard DMX512 Protocol, RDM Protocol
- Data connection: waterproof three-core XLR input/output
- Display: OLED display operation panel
- Convenient and fast upgrade through DMX signal update software

## APPLICATION

- Silent waterproof fan, intelligent speed regulation
- Temperature intelligent protection to ensure the service life of LED
- Fan heat dissipation
- Protection level: IP65
- Working environment: -40°C ~ 45°C

