

SP-PIXEL LINE IP EFFECT FIXTURE



LIGHT SOURCE

- 672 pieces 0.5W RGB LED
- 112 pieces 3W CW LED
- Voltage: AC100~240V 50/60HZ
- Power Supply: 420W

CONTROL

- 4 Touch Buttons
- Control Panel: 1.77 color screen display
- Control Protocol: DMX512, RDM, Art-Net, sACN
- DMX Channel Mode: 11
- Control Channel:
7/15/21/39/112/17/33/65/68/117/70
- Software Update: DMX Connection

WORKING ENVIRONMENT

- Maximum Ambient Temperature: 40°C
- Minimum Operating Temperature: -10°C
- Maximum Surface Temperature: 65°C
- Protection Level: IP66

FEATURES

Colored light beam angle: 101°
White light beam angle: 108°

Colored light spot angle: 149°
White light spot angle: 152°

- Colored light 32 zones can be controlled individually
- White light 16 zones can be controlled individually
- Excellent color mixing function
- Powerful high-output strobe effect
- Built-in splicing pins for fast splicing and alignment
- Electronic atomization effect
- 0-100% smooth dimming function
- Efficient optical system

Lighting Specifications

Length: 1,000mm (39.4")

Width: 139 mm (4.9")

Height: 90 mm (3.5")

Lighting Net Weight: 8.6 kg (19 lbs)



No. 16, Jalan Budiman, Budiman Business Park, 43000 Kajang, Selangor, Malaysia



+6016-446-5555



www.spartanlightings.com

Follow us on:



[Learn More
On Our Website](#)

