

# SP-LED 600W UV LED WASH



## DIMENSIONS & WEIGHT

- Dimensions: 558 × 147 × 380 mm
- Weight: 15.5 kg

## POWER SUPPLY

- Input voltage: AC 90–240V, 50/60Hz
- Power consumption: 600W

## LIGHT SOURCE

- High-power 600W LED output
- 60 pcs USA CREE 4-in-1 LEDs
- UV customizable light source

## OPTICAL SYSTEM

- DMX512 interface (3-core / optional 5-core).
- Power cord with hand-in-hand socket.

## OPERATION MODES

Non-spherical lens with individual LED control for strip effects like strobe and chase, with built-in programs.

## IP RATING

IP65



# SP-LED 600W UV

## CONTROL & PROGRAMMING

- DMX control mode
- DMX channel modes: 4CH / 6CH / 9CH
- Auto Run mode (Jump / Fade / Pulse)
- Manual colour & UV control
- Macro effect mode
- Master-Slave operation
- RDM-enabled configuration
- Digital menu navigation
- Full-color display screen
- Digital / LCD display panel
- Multi-language interface (Chinese / English)
- Screen rotation on/off
- Screen saver on/off
- Logo display on/off

## OPERATIONAL FEATURES & PERFORMANCE

- Linear dimming from 0-100%
- Adjustable RGBW current control
- Stable brightness performance
- System test function
- System information display
- Runtime and total usage time display
- Real-time temperature display

## DIMENSION SKETCH

