

SP-420 BEAM-IP BEAM



DIMENSION & NET WEIGHT

- Dimension : 372 x 312 x 631 mm
- Net Weight : 23 kg

LIGHT SOURCE & LIFE LAMP

- OSRAM SIRIUS HRI 420WS
- Color temperature: 7500K $\pm$ 200K
- Life Lamp : 4,000 hours

ACCESSORIES

G clamp, safety cable, flight case (optional), OMEGA

CONTROL

DMX512, RDM

Control Signal: DMX512, RDM

DMX Channel: 16 Channel

POWER & SIGNAL CONNECTION

- Voltage: AC 100V~240V/50~60Hz
- Power: 650W
- Power cable (powercon) Signal input/output cables(xlr cable)

SAFETY & COMPLIANCE

- Protection grade: IP55
- Cooling method: Air-cooled
- Error alarm: Automatic alarm for lamp failure



No. 16, Jalan Budiman, Budiman Business Park, 43000 Kajang, Selangor, Malaysia



+6016-446-5555



www.spartanlightings.com

Follow us on:



[Learn More
On Our Website](#)



SP-420 BEAM-IP

FEATURES

- Output lens diameter: 200MM
- Pan: 540° (16bit)
- Tilt: 270° (16bit)
- Beam angle: 1.2°
- Dimmer: 0-100%
- Strobe: 0-25Hz

APPLICATION

The entire fixture is waterproof and dustproof, suitable for outdoor use in various environments

EFFECT

- Color: 14 color filters + white light (half-color effect available)
- Gobo: 17gobo + white light
- Prism: 8 prism, 8+8+8 honeycomb prisms (double prisms can be stacked to 32, and can rotate independently in both directions)
- Frost: 10°Frost, soft and natural light spot

