SP-TORNADO IP

LED WASH

LIGHT SOURCE & OPTICS

- Main LED: 5 × 120W RGBL
- Outer Circle: 120 × 0.5W RGB LEDs
- LED Life: 20,000 hours
- Beam Angle: 3°–30°
- Field Angle: 4°–35°
- CTO: 2500K–8000K

POWER & ELECTRICAL

- Voltage: AC 100–240V, 50/60Hz
- Power Consumption: 800W

MOVEMENT

- Pan: 59° / 16-bit
- Tilt: 221° / 16-bit
- Dimmer: 0–100% / 16-bit
- Strobe: 1–30Hz

CONTROL

- DMX Channels: 41 / 51 / 71 / 79CH
- Control Modes: DMX512 / RDM / sACN
- Display: LCD Display

PROTECTION

- Protection Rating: IP66

POWER & ELECTRICAL

- Voltage: AC 100–240V, 50/60Hz
- Power Consumption: 800W

DIMENSION & NET WEIGHT

- Dimensions: 1002 × 196 × 334 mm
- Net Weight: 32 kg

No. 16, Jalan Budiman, Budiman Business Park, 43000 Kajang, Selangor, Malaysia

+6016-446-5555 www.spartanlightings.com Follow us on:

Learn More On Our Website